

## V6 Vertical Windlass

- All stainless steel deck unit
- Powered and manual chain release
- For boats up to 24m (80ft)
- Cone Clutch for smooth, easy control
- Left- and right-hand versions
- Available in 24 V and Hydraulic power options
- Lloyd's Type Approval
- W.A.R.P. Drum (Wear and Abrasion Resistant Pattern)
- Remote chain-pipe version – For use with any size chain, but recommended when using 14mm chain



### V6 Electric Specifications

MODEL	MOTOR POWER	MAX PULL		WORKING LOAD LIMIT		MAX LINE SPEED		NORMAL CURRENT DRAW	CIRCUIT BREAKER	WEIGHT	
	Watt	kg	lb	kg	lb	m/min	ft/min	Amp	Amp	kg	lb
V6 24V	2000	1818	4000	606	1333	18	59	90	150	63	139

### V6 Hydraulic Specifications

PRODUCT	NORMAL PRESSURE	FLOW RATE	MAX. PULL		MAX. LINE SPEED		WEIGHT	
			kg	lb	m/min	ft/min	kg	lb
V6 Hydraulic	60 bar 882 psi (cont)	20-60 l/min 5.2-15.8 US gal/min	1450 at 190 bar	3190 at 2793 psi	34 at 60 l/min	110 at 15.9 US gal/min	52	114

### V6 Part Numbers

#### 1 Deck Unit



PART NO.	DESCRIPTION
69000400	V6 Deck Unit LH Gypsy Drum
69000401	V6 Deck Unit RH Gypsy Drum
69000402	V6 Deck Unit LH Gypsy Only
69000403	V6 Deck Unit RH Gypsy Only
69000404	V6 Deck Unit UNI Gypsy /Drum
69000405	V6 Deck Unit UNI Gypsy Only

LH = Left Hand, RH = Right Hand, UNI = Universal (symmetrical version)

#### 2 Motor Gearbox



PART NO.	DESCRIPTION
69000407	V6 - 24V Motor/Gearbox Assy
69000408	V6 - Hyd Motor/Gearbox
69000409	V6 Hi-Pressure Hyd Motor/Gearbox



#### 3 Gypsy



PART NO.	CHAIN DESCRIPTION
68000903	10mm DIN 766, 3/8" ISO G4, Lewmar 9.5mm G40
68000904	11mm Short Link, Lewmar 12mm G30/G40, 13mm DIN 766
68000905	Lewmar 14mm G30/G40, 14mm DIN 766, 7/16" G40 Recommend remote chain pipe version
68000906	1/2" ISO G4, Lewmar 12mm G30/G40, Lewmar 1/2" G30/G40

